

RL31N

L-3/E-3



SUPERIOR TRACTION AND STABILITY; LONG LASTING PERFORMANCE

- **Non-directional multiblock tread pattern and open shoulder grooves; Ultra-wide tread**

Benefit: To provide superior traction and stability.

- **Double-reinforcement tie-bars**

Benefit: To deliver better center-block strength and improved wear resistance.

- **High tensile steel belt package built in**

Benefit: To resist impacts and minimize damages.

- **Super thick tread base and thickened sidewalls.**

Benefit: Better cut and puncture resistance.



| Size | Star Rating | TRA Code | Rim | Section width | | Overall Diameter | | Tread Depth | Load Index & Speed Symbol | Standard Inflation Pressure (kPa) | Type |
|---------|-------------|----------|-----------|---------------|-----|------------------|------|-------------|---------------------------|-----------------------------------|------|
| | | | | in | mm | in | mm | | | | |
| 17.5R25 | ★★ | L-3/E-3 | 14.00/1.5 | 17.52 | 445 | 53.14 | 1350 | 28 | 182A2/167B | 600 | TL |
| 20.5R25 | ★★ | L-3/E-3 | 17.00/2.0 | 20.47 | 520 | 58.66 | 1490 | 32 | 193A2/177B | 600 | TL |
| 23.5R25 | ★★ | L-3/E-3 | 19.50/2.5 | 23.43 | 595 | 63.58 | 1615 | 35 | 201A2/185B | 600 | TL |
| 26.5R25 | ★★ | L-3/E-3 | 22.00/3.0 | 26.57 | 675 | 68.90 | 1750 | 40 | 209A2/193B | 600 | TL |
| 29.5R25 | ★★ | L-3/E-3 | 25.00/3.5 | 29.53 | 750 | 73.74 | 1875 | 40 | 216A2/200B | 600 | TL |